PRODUCT DATA SHEET

Model: **IEZAT1.5S**

Split-System Air-Cooled
1.5 Ton Chiller



Legacy Chiller Systems

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464





User-Friendly


with Stainless Steel Tank



STANDARD ON ALL LEGACY CHILLER MODELS:

Pentra Microsmart, Programmable Logic Controller (PLC) with HMI Touch Screen Display.

Condenser Model (OC1.5S)



OC Refrigerant Connections: Discharge Line- 1/2", Liquid Line- 3/8"

Standard Features:

- ETL listed to UL1995 & CAN/CSA C22.2
 No. 236-11, 4th edition, 10/14/2011
- Single Point Power Connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- · STAINLESS STEEL, brazed plate evaporator
- · Scroll compressor with crankcase heater
- Suction Accumulator
- · Water flow switch
- Hot Gas Bypass Capacity Control
- 24V control transformer
- · Control circuit fusing
- Compressor motor contactor
- Painted Powder Coated (Most Models), galvanized sheet metal cabinet
- 1/2" insulation on all water and refrigerant lines
- · Liquid line drier, sight glass, solenoid, TXV
- · Complete refrigerant charge from factory
- Factory Performance Test prior to shipment
- Extended warranty: See your quote or latest IOM booket revision

Tank

- STAINLESS STEEL storage tank with 1/2 inch insulation
- Fused, STAINLESS STEEL re-circulation pump for tank operation with ball valve and cleanable strainer
- Tank pressure relief valve, vent and drain hose bibs

Easy to Use Touch Screen Display on all Legacy Chiller Models



Options:

- Copeland Digital Scroll Compressor
- Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control on primary compressor
- 4 year extended compressor warranty
- · Condenser water regulating valve
- 115 volt (rain tight) service outlet
- · Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- Compressor fusing
- · Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- · Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- Dual system pump with manual changeover (some models)
- Dual system pump with auto changeover (some models)
- Pump suction isolation valve
- · Water pressure gauge set
- · Water Flow Meter
- Auto city water changeover panel with filter
- Stainless steel, SCH80 PVC or Polypropylene piping for deionized and reverse osmosis water systems
- Door Mounted HMI with weather proof cover

Tank Options

- Storage tank sight glass
- · Tank low liquid level indicator with dry contacts
- Auto Tank Fill

PRODUCT DATA SHEET

Model: **IEZAT1.5S**Split-System Air-Cooled

1.5 Ton Chiller



Legacy Chiller Systems 851 Tech Drive

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

with Stainless Steel Tank

Dimensional & Electrical Table (Single Circuit)

Chiller	Length	Width Inches	Height Inches	Power			Compressor		RLA	LRA	RA Fan Motor		Recirculation			Reservoir	Chiller	Weight	Condenser
Models	Inches			Voltage	Phase	Freq.	Qty.	НР	ea.	ea.	Qty.	FLA.	Pump FLA	MCA	M.O.P	Gal.	Fluid Conn.	LBS.	Selection
IEZAT1.5SE5		34	65	208/230V	1	60Hz	1	2.0	13.5	68	1	3.8	4.2	25	35	20	1" FPT	600	
IEZAT1.5SF5	36			208/230V	3	60Hz			8.0	58		3.8	4.2	20	25				OC1.5S
IEZAT1.5SH5	30			460V	3	60Hz			4.2	29		1.5	0.9	15	15		I FPI	600	001.55
IEZAT1.5SI5				575V	3	60Hz			3.1	24		1.72	0.72	15	15				

Capacity Table (Refrigerant R407C)

Model	Compressor	LWT °F	80°F			90°F			95°F			100°F			105°F		
			TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
1.5\$	ZS15KAE	*42.0	1.7	1.7	8.9	1.6	1.8	7.9	1.5	1.9	7.4	1.5	2.0	7.0	1.4	2.2	6.5
		*44.0	1.7	1.7	9.1	1.6	1.9	8.1	1.6	2.0	7.6	1.5	2.1	7.2	1.5	2.2	6.7
		45.0	1.8	1.7	9.3	1.7	1.9	8.3	1.6	2.0	7.7	1.6	2.1	7.3	1.5	2.2	6.8
		50.0	2.0	1.8	9.9	1.9	1.9	8.8	1.8	2.0	8.3	1.8	2.1	7.8	1.7	2.2	7.3

* = Requires the use of glycol.

Product Dimensional Drawing

ACCESS PANEL

ACCESS PANEL

REFRIGERANT DISCHARGE LINE

REFRIGERANT LIQUID LINE

18.0 **I**n



