

PRODUCT DATA SHEET

Model: IEZAT13D
Split-System Air-Cooled
13 Ton Chiller



Legacy Chiller Systems
851 Tech Drive
Telford, PA 18969
Toll-Free: (877) 988-5464




User-Friendly
Touch Screen
Display

with Stainless Steel Tank



STANDARD ON ALL LEGACY CHILLER MODELS:
Pentra Microsmart, Programmable Logic Controller (PLC)
with HMI Touch Screen Display.

Condenser Model (OC13D)



OC Refrigerant Connections: Discharge Line- 7/8" (2), Liquid Line- 1/2" (2)

Standard Features:

- ETL listed to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- Single point power connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- STAINLESS STEEL, brazed plate evaporator
- Scroll compressor with crankcase heater
- Suction accumulator
- Water flow switch
- Hot gas by-pass capacity control
- 24V control transformer
- Direct drive condenser fan motor
- Rust resistant, high CFM, aluminum condenser fan blade
- Condenser(s): copper tube/ aluminum fin
- Compressor motor contactor
- Condenser motor and control circuit fusing
- Painted (Powder Coated), galvanized sheet metal cabinet
- 1/2" insulation on all water and Low pressure refrigerant lines
- Liquid line drier, sight glass, solenoid, TXV
- Complete refrigerant charge from factory
- Factory Performance Test prior to shipment
- Extended warranty: See your quote or latest IOM booklet revision



Easy to Use
Touch Screen Display
on all Legacy Chiller
Models

Tank

- STAINLESS STEEL storage tank with 1/2 inch insulation
- Fused, STAINLESS STEEL re-circulation pump for tank operation with ball valve and cleanable strainer
- Tank pressure relief valve, vent and drain hose bibs

Options:

- Copeland Digital Scroll Compressor
- Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control on primary compressor
- 4 year extended compressor warranty
- Casters (factory mounted)
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- Compressor fusing
- Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- Dual system pump with manual changeover (some models)
- Dual system pump with auto changeover (some models)
- Pump suction isolation valve
- Water pressure gauge set
- Water Flow Meter
- Auto city water changeover panel with filter
- Door Mounted HMI with weather proof cover

Tank Options

- Storage tank sight glass
- Tank low liquid level indicator with dry contacts
- Auto Tank Fill

PRODUCT DATA SHEET

Model: IEZAT13D
 Split-System Air-Cooled
 13 Ton Chiller



Legacy Chiller Systems
 851 Tech Drive
 Telford, PA 18969
 Toll-Free: (877) 988-5464

Dimensional & Electrical Table (Dual Circuit)

Chiller Models	Length Inches	Width Inches	Height Inches	Power			Compressor		RLA ea.	LRA ea.	Fan Motor		Recirculation Pump FLA	MCA	M.O.P.	Reservoir Gal.	Chiller Fluid Conn.	Weight Pounds	Condenser Model
				Voltage	Phase	Freq.	Qty.	HP			Qty.	FLA							
IEZAT13DF5	75	34	70	208/230V	3	60Hz	2	8	28.8	195	2	3.8	3.5	80	100	80	1.5" FPT	1700	OC13D
IEZAT13DH5				460V	3	60Hz			14.7	95		1.5							
IEZAT13DI5				575V	3	60Hz			10.8	80		1.72							

Capacity Table (Refrigerant R407C)

Model	Compressor	LWT °F	80°F			90°F			95°F			100°F			105°F		
			TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
13D	ZB58KCE	*42.0	12.0	11.8	12.5	11.7	13.1	10.8	11.3	13.8	10.1	10.9	14.5	9.4	10.4	15.3	8.7
		*44.0	12.6	11.9	12.8	12.2	13.2	11.2	11.8	13.9	10.4	11.4	14.6	9.7	10.9	15.4	9.0
		45.0	12.8	12.0	13.0	12.5	13.3	11.3	12.1	14.0	10.6	11.7	14.7	9.8	11.2	15.5	9.2
		50.0	14.3	12.3	13.7	13.9	13.6	12.0	13.5	14.3	11.2	13.1	15.0	10.5	12.6	15.8	9.8

* = Requires the use of glycol.

Product Dimensional Drawing

