

PRODUCT DATA SHEET

Model: PZATN13D

*Packaged Air-Cooled
13 Ton Chiller*




Legacy Chiller Systems

851 Tech Drive
Telford, PA 18969

Toll-Free: (877) 988-5464

with Stainless Steel Tank



Side/Front View

Back View

STANDARD ON ALL LEGACY CHILLER MODELS:
Idec Microprocessor Controller
with Touch Screen Display
(located inside electrical cabinet)

Standard Features:

- ETL listed to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- Single point power connection
- Idec microprocessor controller with easy to use touch screen display
- Included with Patented **ECONOMIZER TECHNOLOGY**
- **STAINLESS STEEL** Tank
- **STAINLESS STEEL**, brazed plate evaporator
- Scroll compressor with crankcase heater
- Suction accumulator
- Water flow switch
- Hot gas by-pass capacity control
- 24V control transformer
- Direct drive condenser fan motor
- Rust resistant, high CFM, aluminum condenser fan blade
- Condenser(s): copper tube/aluminum fin
- Compressor motor contactor
- Condenser motor and control circuit fusing
- Painted (Powder Coated), galvanized sheet metal cabinet
- 1/2" insulation on all water and Low pressure refrigerant lines
- Liquid line drier, sight glass, solenoid, TXV
- Complete refrigerant charge from factory
- **Factory Performance Test prior to shipment**
- **5 Year Limited Warranty**

*Easy to Use
Touch Screen Display
on all Legacy Chiller
Models*



Options:

- Copeland Digital Scroll Compressor
- Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control
- 4 year extended compressor warranty
- Casters (factory mounted)
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and High/Low voltage
- Compressor fusing
- Tank Sight Glass
- Compressor Sound Cover
- Flooded cond. w/receiver/head pressure control (0°F)
- Heated, flooded cond. w/receiver/head pressure Water flow meter control (-20°F)
- Dual process pump with auto changeover
- Pump suction isolation valve
- Water pressure gauge set
- Copper finned condenser coil (coastal protection)
- Coastal powder coat paint protection
- E-Coat Condenser Coil (coastal protection)
- Water Flow Meter
- Auto city water make up solenoid & auto level switch
- Auto city water changeover panel with filter
- Storage tank sight glass
- Door Mounted HMI with weather proof cover

PRODUCT DATA SHEET

Model: **PZATN13D**
Packaged Air-Cooled
13 Ton Chiller



Legacy Chiller Systems
 851 Tech Drive
 Telford, PA 18969
 Toll-Free: (877) 988-5464

with Stainless Steel Tank

Dimensional & Electrical Table (Dual Circuit)

Chiller Models	Length Inches	Width Inches	Height Inches	Power			Compressor		RLA ea.	LRA ea.	Fan Motor		Recirculation Pump	MCA	M.O.P	Reservoir Gal.	Chiller Fluid Conn.	Weight Pounds	
				Voltage	Phase	Freq.	Qty.	HP			Qty.	FLA.							
PZATN13DF5	85	40	76	208/230V	3	60Hz	2	8	28.8	195	2	3.8	3.5	80	100	80	1.5" FPT	1300	
PZATN13DH5				460V	3	60Hz			14.7	95		1.5		40					50
PZATN13DI5				575V	3	60Hz			10.8	80		1.72		30					35

Capacity Table (Refrigerant R407C)

Model	Compressor	LWT °F	80°F			90°F			95°F			100°F			105°F		
			TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
13D	ZB58KCE	*42.0	12.0	11.8	12.5	11.7	13.1	10.8	11.3	13.8	10.1	10.9	14.5	9.4	10.4	15.3	8.7
		*44.0	12.6	11.9	12.8	12.2	13.2	11.2	11.8	13.9	10.4	11.4	14.6	9.7	10.9	15.4	9.0
		45.0	12.8	12.0	13.0	12.5	13.3	11.3	12.1	14.0	10.6	11.7	14.7	9.8	11.2	15.5	9.2
		50.0	14.3	12.3	13.7	13.9	13.6	12.0	13.5	14.3	11.2	13.1	15.0	10.5	12.6	15.8	9.8

* = Requires the use of glycol.



Product Dimensional Drawing

